



Important Notice to our Customers

Product Change Notice #: VI20220114

Date: January 14, 2022

To Our Valued Customer:

This is to inform you of specification change to four MVTM36 series and four VTM48 series products.

PCN Type:

Change of electrical specification

Products Affected:

MVTM36Bx360M003A00

MVTM36Bx240M005A00

MVTM36Bx180M007A00

MVTM36Bx120M010A00

VTM48Ex480y006A00

VTM48Ex320y009A00

VTM48Ex160y015A00

VTM48Ex240y012A00

Proposed Change:

Electrical specification changes:

Product Number	Specs Change			From			To			Unit
	Attribute	Symbol	Conditions / Notes	Min	Typ	Max	Min	Typ	Max	
MVTM36B360M003A00	Output Resistance (Cold)	ROUT_COLD	T _C = -40°C, I _{OUT} = 3A	55.0	108.0	175.0	30	80	175	mΩ
	Output Resistance (Ambient)	ROUT_AMB	T _C = 25°C, I _{OUT} = 3A	112.0	140.0	168.0	72	100	168	mΩ
	Output Resistance (Hot)	ROUT_HOT	T _C = 100°C, I _{OUT} = 3A	152.0	190.0	228.0	120	160	228	mΩ
VTM48EF480T006A00	Efficiency (Ambient)	η _{AMB}	V _{IN} = 26 - 55V, I _{OUT} = 6.3A	93.3			92.8			%
VTM48EF320T009A00	Efficiency (Ambient)	η _{AMB}	V _{IN} = 26 - 55V, I _{OUT} = 9.4A	93.0			92.5			%

Signal Characteristic changes:

Datasheet Rev. 1.8, 1.5, 1.5, 1.7 (page 4)

Product Number	Signal Type	State	Attribute	Symbol	Conditions / Notes	Min	Typ	Max	Unit
VTM48Ex480y006A00	Analog Input	Steady	VC Current Draw	I _{vc}	VC = 11.5V, V _{IN} > 26V		0		mA
VTM48Ex320y009A00					VC = 16.5V, V _{IN} > 26V		0		
VTM48Ex160y015A00		VTM48Ex240y012A00	Transitional	VC to Vout Turn-On Delay	ton	V _{IN} pre-applied, PC floating, VC enable, C _{PC} = 0μF			500

Datasheet Rev. 1.9, 1.6, 1.6, 1.8 (page 4)

Product Number	Signal Type	State	Attribute	Symbol	Conditions / Notes	Min	Typ	Max	Unit
VTM48Ex480y006A00	Analog Input	Steady	VC Current Draw	I _{vc}	VC = 11.5V, V _{IN} > 26V		22.5		mA
VTM48Ex320y009A00					VC = 16.5V, V _{IN} > 26V		32		
VTM48Ex160y015A00		VTM48Ex240y012A00	Transitional	VC to Vout Turn-On Delay	ton	V _{IN} pre-applied, PC floating, VC enable, C _{PC} = 0μF, C _{OUT} = 0μF			500

Datasheet Rev. 1.4 (page 16)

Product Number	Signal Type	State	Attribute	Symbol	Conditions / Notes	Min	Typ	Max	Unit
MVTM36Bx360M003A00	Analog Input	Steady	VC Current Draw	I _{vc}	VC = 13V, V _{IN} = 0V			150	mA
MVTM36Bx240M005A00		Start Up	VC Inrush Current	I _{INR_VC}	VC = 16.5V, dVC/dt = 0.25V/μs			750	
MVTM36Bx180M007A00		VTM36Bx120M010A00	Transitional	VC to Vout Turn-On Delay	ton	V _{IN} pre-applied, PC floating, VC enable, C _{PC} = 0μF, C _{OUT} = 4000μF			500

Datasheet Rev. 1.5 (page 16)

Product Number	Signal Type	State	Attribute	Symbol	Conditions / Notes	Min	Typ	Max	Unit
MVTM36Bx360M003A00	Analog Input	Steady	VC Current Draw	I _{VC}	V _C = 13V, V _{IN} = 0V			200	mA
MVTM36Bx240M005A00		Start Up	VC Inrush Current	I _{INR_VC}	V _C = 16.5V, dV _C /dt = 0.25V/μs			2	A
MVTM36Bx180M007A00		Transitional	VC to Vour Turn-On Delay	ton	V _{IN} pre-applied, PC floating, V _C enable, C _{PC} = 0μF, C _{OUT} = 0μF			500	μs

Reason for the change:

For yield improvement.

Effective Date:

The new specifications are effective immediately.

Actions Required:

Customers should make note of the change and contact Applications Engineering with any questions or concerns.

Company contact for technical questions:

Applications Engineering Vicor Corporation
 25 Frontage Road
 Andover, MA
 Phone: (978) 470-2900
apps@vicorpower.com